

HAND and POWER SWAGERS

for assembling end connections
on **SWAGELOK®** Thermoplastic Hose

HAND SWAGER

for quality hose assemblies where electrical power
is not available



- use to assemble 1/4", 3/8", 1/2", and 3/4" hose
- rugged, die-cast aluminum construction
- portable for field assembly
- weight: 8 lb
- bench mountable
- immediate availability

Ordering Number: MS-HSR



CARRYING CASE

for carrying Hand Swager
and custom-ordered accessories
(see reverse side)

Ordering Number: MS-HSR-CASE

POWER SWAGER

for efficient, high-speed assembly

- ready to use
- simple operation – operator can be trained quickly
- unique design – allows dies to open and close automatically
- fast assembly – only seconds per end connection
- bench mountable

weight: 132 lb
height: 30"
width: 14"
depth: 25"



Ordering Numbers:
MS-PSR-110 (1HP, 60HZ, 115/208/230V Single Phase Motor)
MS-PSR-220 (1HP, 50HZ, 230V Single Phase Motor)

Complete Hose Assembly Instructions
come with each unit.




SWAGELOK Quick-Connect Co.
Hudson, Ohio 44236 U.S.A.

ACCESSORIES

ORDERING INFORMATION

		FOR END CONNECTION...	USE PUSHER® ORDERING NUMBER...	AND DIE® ORDERING NUMBER...
SWAGELOK TUBE ADAPTER (Fractional)		TP4-TA4 TP4-TA6 TP6-TA6 TP8-TA8 TP8-TA10 TP12-TA12 TP16-TA16 TP16-TA16	MS-P-TA4 MS-P-4TA6 MS-P-TA6 MS-P-SLTA8 MS-P-8TA10 MS-P-TA12 MS-P-TA16 MS-P-TA16	MS-7R8R-4 MS-7R8R-4 MS-7R8R-6 MS-7R8R-8 MS-7R8R-8 MS-8R-12 MS-8R-16 MS-7P-16 [®]
SWAGELOK TUBE ADAPTER (Metric)		TP4-TM6 TP4-TM8 TP6-TM10 TP8-TM12	MS-P-TA4 MS-P-4TM8 MS-P-TA6 MS-P-SLTA8	MS-7R8R-4 MS-7R8R-4 MS-7R8R-6 MS-7R8R-8
SWAGELOK TUBE FITTING (Fractional)		TP4-SL4 TP6-SL6 TP8-SL8	MS-P-SL4 MS-P-SL6 MS-P-SLTA8	MS-7R8R-4 MS-7R8R-6 MS-7R8R-8
SWAGELOK TUBE FITTING (Metric)		TP4-SM6 TP4-SM8 TP4-SM10 TP6-SM10 TP8-SM12	MS-P-SL4 MS-P-4SM8 MS-P-4SM10 MS-P-SL6 MS-P-SLTA8	MS-7R8R-4 MS-7R8R-4 MS-7R8R-4 MS-7R8R-6 MS-7R8R-8
MALE BSP/ISO PARALLEL (RS)		TP4-MS4 TP6-MS6 TP8-MS8	MS-P-MS4 MS-P-MS6 MS-P-MS8	MS-7R8R-4 MS-7R8R-6 MS-7R8R-8
MALE BSP/ISO TAPERED (RT)		TP4-MT4 TP6-MT6 TP8-MT8	MS-P-PM4 MS-P-PM6 MS-P-PM8	MS-7R8R-4 MS-7R8R-6 MS-7R8R-8
JIC (AN) 37° FEMALE SWIVEL		TP4-AS4 TP6-AS6 TP8-AS8	MS-P-AS4 MS-P-AS6 MS-P-AS8	MS-7R8R-4 MS-7R8R-6 MS-7R8R-8
MALE NPT		TP4-PM4 TP6-PM4 TP6-PM6 TP8-PM8	MS-P-PM4 MS-P-PM6 MS-P-PM6 MS-P-PM8	MS-7R8R-4 MS-7R8R-6 MS-7R8R-6 MS-7R8R-8
60° MALE CONE BSP/ISO FEMALE SWIVEL		TP4-BM4 TP6-BM6 TP8-BM8	MS-P-BM4 MS-P-BM6 MS-P-BM8	MS-7R8R-4 MS-7R8R-6 MS-7R8R-8
30° FEMALE SWIVEL BSP/ISO/JIS BSP/ISO PARALLEL THREADS		TP4-BS4 TP6-BS6 TP8-BS8	MS-P-BS4 MS-P-BS6 MS-P-BS8	MS-7R8R-4 MS-7R8R-6 MS-7R8R-8
UNIVERSAL METRIC FEMALE SWIVEL [®]		TP4-MC14 TP6-MC18 TP8-MC22	MS-P-MC14 MS-P-MC18 MS-P-MC22	MS-7R8R-4 MS-7R8R-6 MS-7R8R-8
QH INTEGRAL STEM [®]		S-TP8-HD8 [®] S-TP8-HS8 [®]	MS-P-HD8	MS-7R8R-8

HAND CUTTER[®]
MS-HC-SC



LUBRICANT[®]
MS-LUB-1700
MS-LUB-G771



**DEPTH
INSERTION
GAGE[®]**
MS-IGB-1
(1/4", 3/8" & 1/2")
MS-IGB-2
(3/4" & 1")



**WISE
BLOCK**
MS-VB-1
(1/4", 3/8" & 1/2")
MS-VB-2
(3/4" & 1")



[®]Mates with DIN 7631/7647 (60° Cone) and L Series 3901/3902 (24° Cone).
[®]SWAGELOK Poly Pure Thermoplastic Hose.

[®]DESO stem contains a shut-off valve.

[®]SESO stem does not contain a shut-off valve.

[®]Required to assemble hose.



Your Local Authorized SWAGELOK Sales & Service Representative:

Printed in U.S.A.
CR (E)
September, 1995